

TI-PROBOARD® FOR TILING DECKS



TI-PROBOARD® is a sustainable, durable composite panel that is unaffected by expansion, contraction or exterior weather conditions. Being virtually maintenance-free means more time to spend with your family!

The Strength Behind the Beauty



All items needed to tile decks

- FinPan TI ProBoard
- FinPan TI-Proboard Screws
- Mortar Mix
- WaterArmor for Decks and FinPan Protecto Wrap Membrane for underdeck living spaces
- FinPan TI-Proboard Edging
- Outdoor grout
- Tile



TI ProBoard is a structural material so there is no other plywood, backer boards etc. required.

Easy Instructions for using TI PROBOARD®

1) Placement of TI ProBoard

Place TI ProBoard on the joists. Screw the first TI-Proboard (with the slot) in from the edge of the deck frame. It is very important to make sure the first board is straight and square. Measure and use a chalk line. Continue by interlocking each board to the next, and screw TI ProBoard down on each joist. Put screws every 4 ribs. Each joist is 16" on center.

2) Joining/ Butting TI ProBoard

Place each end equal distance on the center of joist. **DO NOT MAINTAIN A CONTINUAL SEAM ALONG THE SAME JOIST- ALL SEAMS ARE TO BE STAGGERED.** No one piece of TI-ProBoard® can be shorter than 3 joist spans.

3) Installing Mortar Mix

Use ANSI A108.1B mortar mix and mix to manufacturer specifications. Trowel mortar level with the tops of the ribs ensuring the ribs fill completely. We recommend using a wet saw when cutting TI ProBoard

4) Protective/Decorative Edging

TI.EDGING™ provides a protective and decorative finish. Install while the thin set mix is still wet. This can be done after the TI ProBoard® has been screwed down and mortar bed applied. Press TI EDGING into the thin set with the long side pressing against the deck board.



TI ProBoard has been fully tested to withstand the temperature differences it is likely to encounter in the USA.

1. JOIST
2. TILE
3. THIN SET
4. WATER PROOFING
5. MORTAR MIX
6. TI-PROBOARD®



www.FinPan.com