



*The Strength  
Behind the Beauty*

# PreFormed® Niches

Waterproof, easy to install  
and ready to tile in minutes.



PreFormed Niches unique in-wall construction can be used throughout the home for an added accent in foyers, kitchens, bar areas as well as the shower.

PreFormed Niches one piece construction and liquid waterproof coating ensure piece of mind in any application.



PF-301/Square  
12" x 12"



PF-304/Wide Combo  
12" x 12" x 6"



PF-305/Narrow Combo  
8" x 12" x 6"



PF-306/Mega  
12" x 20"



PF-308/Soap  
8" x 8"

PF-301, 304 & 306 are designed to fit 16" o.c. framing  
Nominal dimensions of interior cavity. See Niche Dimension Sheet for exact specs.



*The Strength  
Behind the Beauty*

## PreFormed® Niches

### Niche Installation

#### One Substrate Layer

Determine desired height of niche and draw level line between studs on outside of substrate layer.

Place niche with the bottom of flange centered on the level line and trace along exterior flange of niche.

Cut along line and remove substrate layer.

Install niche to cross bracing and studs using a polyurethane adhesive/sealant. FinPan specifies SIKa brand Sikaflex 11 FC. Silicone should never be used.

Treat exterior joint with polyurethane sealant to ensure waterproof integrity.

Install tile using a modified thinset mortar.

#### Two Substrate Layer

Determine desired height of niche and draw level line on between studs on outside substrate layer.

Place niche with the bottom of the box centered on the level line and trace outline of the back of niche box.

Cut through both layers along line and remove layers.

Place niche into opening and trace exterior flanges.

Remove niche and set aside.

Cut through outside layer only and remove "picture frame" outline.

Install niche using a polyurethane adhesive/sealant.

Treat exterior joint with polyurethane sealant to ensure waterproof integrity.

Install tile using a modified thinset mortar.

Custom niches available for larger projects.

