

PreFormed Niche

DS-PREFNICHE-080723

Data Sheets are subject to change without notice. For latest revision, visit our website at www.finpan.com

1. PRODUCT NAME

FinPan PreFormed Niche

2. MANUFACTURER

FinPan, Inc.

3255 Symmes Road

Hamilton, OH 45015

| Telephone: | | 1-513-870-9200 |
|------------|---|----------------|
| Toll Free: | | 1-800-833-6444 |
| Fax: | | 1-513-870-9606 |
| | ~ | |

Internet www.finpan.com 3. PRODUCT DESCRIPTION

PreFormed Niches are constructed of lightweight highdensity expanded polystyrene and a liquid waterproof membrane finish. PreFormed Niches are 100% waterproof and ready-to-tile.

Materials: Saw or utility knife for cutting substrate layer out of for niche location. Polyurethane adhesive/sealant for adhering niche to studs and waterproofing joints. Modified thinset for setting tile or stone.

Advantages

• Lightweight and durable.

• Factory installed, code approved waterproofing meets ANSI A118.10 requirements

- Ready-to-tile
- Multiple design options
- Fin Pan 20-Year Limited Warranty

Uses

- Interior and Exterior
- Showers and tub surrounds
- Kitchens, entry ways or anywhere an in-wall nook is desired.

• Residential and commercial

Suitable Substrates

• Wood or metal studded walls

PreFormed Niche Models (Cavity Dimensions)

PF-301 / Square 12" x 12" (30 cm x 30 cm)

PF-304/ Wide Combo 12" x 12' & 12" x 6" (30 cm x 30 cm & 30 cm x 15 cm)

PF-305 / Narrow Combo 8" x 12" & 8" x 6" (20 cm x 30 cm & 20 cm x 15 cm)

PF-306 / Mega 12" x 20" (30 cm x 51 cm) PF-308 / Soap 8" x 8" (20 cm x 20 cm)

Shelf Life

• Factory sealed boxes are guaranteed to be of first quality for five (5) years if stored at temperatures >32°F (0°C) and <100°F (43°C).

Limitations

- Mastics and silicones are never to be used.
- Don't expose to rubber solvents or ketones.
- Don't expose to sun or weather.

• Must be covered with ceramic tile, stone or latex paint finish.

• Surfaces must be structurally sound, stable and rigid enough to support ceramic/stone tile, thin brick and similar finishes.

Cautions

Consult MSDS for safety information.

• If waterproof coating on the PreFormed Niche is punctured during installation re-coat the punctured area and 2" (50 mm) around the area with two coats of a liquid waterproofing.

4. TECHNICAL DATA

Waterproofing membrane meets ANSI A118.10 5. INSTALLATION

Installation to existing 2 x 4 wall with wall board

• Determine desired height of niche and draw level line on substrate layer.

• Place niche with the bottom flange of the box centered on the level line.

• Trace exterior flanges.

• Cut along line and remove substrate layer. If accessible, install 2 X 4 horizontal cross bracing to support niche.

• Use polyurethane adhesive/sealant to adhere niche to studs.

• Seal joints between niche and backer board using polyurethane adhesive/sealant. Alternatively apply fiberglass mesh and a liquid waterproof membrane.

Installation in New Construction

• Determine desired height of niche and mark 2 x 4 accordingly.

• Install horizontal cross bracing to support niche.

• Use polyurethane adhesive/sealant to adhere niche to studs.

• Next, install $\frac{1}{2}$ " backer board on all walls and flush to niche $\frac{1}{2}$ " flanges.

• Seal joints between niche and backer board using polyurethane adhesive/sealant. Alternatively apply fiberglass mesh and a liquid waterproof membrane. **Tile Installation Detail**

Install tile using a modified thinset and in accordance with the Tile Council of North America (TCNA) guidelines.
AVAILABILITY AND COST

Availability

FinPan products are available worldwide. For Distributor information call:

Toll Free: 1-800-833-6444 Telephone: 1-513-870-9200

Cost: Contact a FinPan Distributor in your area 7. WARRANTY Contact FinPan

8. MAINTENANCE

PreFormed Niches require no maintenance.

9. TECHNICAL SERVICES

Technical Assistance

Information is available by calling FinPan Monday thru Friday from 8:00 AM to 5:00 PM EST.

Technical and Safety Literature

Please visit our website at www.finpan.com.

10. FILING SYSTEM

Information is available at www.finpan.com.