



*The Strength
Behind the Beauty*

WaterArmor® Liquid Waterproofing & Crack Isolation Membrane

WaterArmor Liquid Waterproofing and Crack Isolation Membrane is a 100% acrylic based, ready to use formula. WaterArmor can be used under thinset tile installations on vertical and horizontal surfaces.

As a crack isolation membrane, WaterArmor can bridge cracks up to 1/8" with fiberglass mesh tape.

WaterArmor can be brushed, rolled or troweled into place. It bonds directly to clean metal, PVC and ABS drain assemblies. It offers a 2 hour dry time before installing tile or second coat application.

WaterArmor meets the requirements of ANSI A-118.10.



WaterArmor Liquid Waterproofing & Crack Isolation Membrane

Product ID
Water025
Water100
Water500

Description
WaterArmor - 1 quart
WaterArmor - 1 gallon
WaterArmor - 5 gallon pail



*The Strength
Behind the Beauty*

WaterArmor® Liquid Waterproofing & Crack Isolation Membrane



WaterArmor meets the requirements of ANSI A-118.10 (specification for waterproof membranes beneath thinset tile and stone). It can be used on commercial and residential interior and exterior applications. Apply over concrete, backerboard, exterior grade plywood (interior dry installations only) and mortar beds.

WaterArmor contains an antimicrobial protection, which inhibits the growth of bacteria, mold or mildew on the surface of the dried membrane.

- 2 hour dry time between applications or tile installation
- Flood test as soon as 24 hours
- Low VOC for LEED projects
- Coverage: 45 ft²/gallon (225 sf/pail) with a thickness of 25 mil wet/20 mil dry layer

